

# MBN1600F17F

## Preliminary Specification

Silicon N-channel IGBT 1700V F version

### FEATURES

- \* Soft switching behavior, low switching loss & low conduction loss :  
Soft low-injection punch-through with trench gate IGBT
- \* Low driving power due to low input capacitance advanced trench MOS gate.
- \* Ultra soft fast recovery diode.
- \* High current rate package.
- \* Low  $R_{th(j-c)}$  & low stray inductance.
- \* RoHS
- \* High thermal fatigue durability

### ABSOLUTE MAXIMUM RATINGS ( $T_C=25^\circ\text{C}$ )

Item	Symbol	Unit	MBN1600F17F
Collector Emitter Voltage	$V_{CES}$	V	1,700
Gate Emitter Voltage	$V_{GES}$	V	$\pm 20$
Collector Current	DC	$I_C$	1,600
	1ms	$I_{CRM}$	3,200
Forward Current	DC	$I_F$	1,600
	1ms	$I_{FRM}$	3,200
Junction Temperature	$T_{vj\ op}$	$^\circ\text{C}$	-50 ~ +150
Storage Temperature	$T_{stg}$	$^\circ\text{C}$	-50 ~ +150
Isolation Voltage	$V_{ISO}$	$V_{RMS}$	4,000(AC 1 minute)
Screw Torque	Terminals (M4/M8)	-	2/15 (1)
	Mounting (M6)	-	6 (2)

Notes: (1) Recommended Value  $1.8 \pm 0.2 / 15^{+0}_{-3} \text{N}\cdot\text{m}$  (2) Recommended Value  $5.5 \pm 0.5 \text{N}\cdot\text{m}$

### ELECTRICAL CHARACTERISTICS

Item	Symbol	Unit	Min.	Typ.	Max.	Test Conditions	
Collector Emitter Cut-Off Current	$I_{CES}$	mA	-	-	5	$V_{CE}=1,700\text{V}, V_{GE}=0\text{V}, T_{vj}=25^\circ\text{C}$	
			-	20	70	$V_{CE}=1,700\text{V}, V_{GE}=0\text{V}, T_{vj}=150^\circ\text{C}$	
Gate Emitter Leakage Current	$I_{GES}$	nA	-500	-	+500	$V_{GE}=\pm 20\text{V}, V_{CE}=0\text{V}, T_{vj}=25^\circ\text{C}$	
Collector Emitter Saturation Voltage	$V_{CE(sat)}$	V	-	2.0	-	$I_C=1,600\text{A}, V_{GE}=15\text{V}, T_{vj}=25^\circ\text{C}$	
			-	2.3	-	$I_C=1,600\text{A}, V_{GE}=15\text{V}, T_{vj}=125^\circ\text{C}$	
			-	2.4	TBD	$I_C=1,600\text{A}, V_{GE}=15\text{V}, T_{vj}=150^\circ\text{C}$	
Gate Emitter Threshold Voltage	$V_{GE(th)}$	V	4.1	5.5	7.1	$V_{CE}=10\text{V}, I_C=160\text{mA}, T_{vj}=25^\circ\text{C}$	
Input Capacitance	$C_{ies}$	nF	-	87	-	$V_{CE}=10\text{V}, V_{GE}=0\text{V}, f=100\text{kHz}, T_{vj}=25^\circ\text{C}$	
Internal Gate Resistance	$R_{G(int)}$	$\Omega$	-	2.25	-	$V_{CE}=10\text{V}, V_{GE}=0\text{V}, f=100\text{kHz}, T_{vj}=25^\circ\text{C}$	
Turn On Delay Time	$t_{d(on)}$	$\mu\text{s}$	-	0.7	TBD	$V_{CC}=900\text{V}, I_C=1,600\text{A}$	
Rise Time	$t_r$		-	0.2	TBD	$L_S=65\text{nH}$ (3)	
Turn Off Delay Time	$t_{d(off)}$		-	1.5	TBD	$R_G(\text{on/off})=4.7/4.7\Omega$ (3)	
Fall Time	$t_f$		-	1.5	TBD	$V_{GE}=\pm 15\text{V}, T_{vj}=150^\circ\text{C}$	
Peak Forward Voltage Drop	$V_F$	V	-	2.0	-	$I_F=1,600\text{A}, V_{GE}=0\text{V}, T_{vj}=25^\circ\text{C}$	
			-	2.2	-	$I_F=1,600\text{A}, V_{GE}=0\text{V}, T_{vj}=125^\circ\text{C}$	
			-	2.25	TBD	$I_F=1,600\text{A}, V_{GE}=0\text{V}, T_{vj}=150^\circ\text{C}$	
Reverse Recovery Time	$t_{rr}$	$\mu\text{s}$	-	0.75	TBD	$V_{CC}=900\text{V}, I_C=1,600\text{A}$	
Turn On Loss	$E_{on}$	J/P	-	0.47	-	$L_S=65\text{nH}$ (3)	
Turn Off Loss	$E_{off}$	J/P	-	1.25	-	$R_G(\text{on/off})=4.7/4.7\Omega$ (3)	
Reverse Recovery Loss	$E_{rr}$	J/P	-	0.55	-	$V_{GE}=\pm 15\text{V}, T_{vj}=150^\circ\text{C}$	
Stray inductance module	$L_{SCE}$	nH	-	10	-	Collector Main to Emitter Main	
Thermal Impedance	IGBT	$R_{th(j-c)}$	K/W	-	-	0.0165	Junction to case
	FWD	$R_{th(j-c)}$	K/W	-	-	0.0255	
Contact Thermal Impedance	$R_{th(c-f)}$	K/W	-	0.008	-	Case to fin	

Notes:(3)  $L_S$  and  $R_G$  are the test condition's values for evaluation of the switching times, not recommended value.

Please, determine the suitable  $R_G$  value after the measurement of switching waveforms (overshoot voltage, etc.) with appliance mounted.


- \* Please contact our representatives at order.
- \* For improvement, specifications are subject to change without notice.
- \* For actual application, please confirm this spec sheet is the newest revision.
- \* ELECTRICAL CHARACTERISTIC items shown in above table are according to IEC 60747-2 and IEC 60747-9.

# MBN1600F17F

Preliminary Specification


## OUTLINE DRAWING

Unit in mm




Weight : 870g

## CIRCUIT DIAGRAM




# MBN1600F17F


Preliminary Specification




Collector Current vs. Collector Emitter Voltage



Collector Current vs. Collector Emitter Voltage




Forward Voltage of free-wheeling diode




$V_{GE}$ - $Q_G$  curve

# MBN1600F17F


## Preliminary Specification




Turn-on loss vs. Collector current



Turn-off loss vs. Collector current




Recovery loss vs. Forward current




Switching time vs. Collector Current

# MBN1600F17F


Preliminary Specification



Turn-on loss vs. Gate Resistance







Turn-off loss vs. Gate Resistance



Recovery loss vs. Gate Resistance



# MBN1600F17F

Preliminary Specification



# MBN1600F17F

Preliminary Specification



# MBN1600F17F

Preliminary Specification

## HITACHI POWER SEMICONDUCTORS

### Notices

1. Since mishandling of semiconductor devices may cause malfunctions, please be sure to read "Precautions for Safe Use and Notices" in the individual brochure before use.
2. When designing an electronic circuit using semiconductor devices, please do not exceed the absolute maximum rating specified for the device under any external fluctuations. And for pulse applications, please also do not exceed the "Safe Operating Area (SOA)".
3. Semiconductor devices may sometimes break down by accidental or unexpected surge voltage, so please be careful about the safety design such as redundant design and malfunction prevention design which don't cause the damage expand even if they break down.
4. In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, life-support-related medical equipment, fuel control equipment and various kinds of safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement. Or consult with Hitachi's sales department staff. (When semiconductor devices fail, as a result the semiconductor devices or wiring, wiring pattern may smoke, ignite, or the semiconductor devices themselves may burst.)
5. A semi-processed article is done now using solder which contains lead inside the semiconductor devices. There is possibility of the regulation substance depend on the applied models, so please check before using.
6. This specification is a material for component selection, which describes specifications of power semiconductor devices (hereinafter referred to as products), characteristic charts, and external dimension drawings.
7. The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact with Hitachi power semiconductor sales department for the latest version of this data sheets.
8. For handling other than described in this manual, follow the handling instructions (IGBT-HI-00002).

- 
- For inquiries relating to the products, please contact nearest representatives that is located "Inquiry" portion on the top page of a home page.
- 

Hitachi power semiconductor home page address

<http://www.hitachi-power-semiconductor-device.co.jp/>

<http://www.hitachi-power-semiconductor-device.co.jp/en/>



# MBN1600F17F

Preliminary Specification

## HITACHI POWER SEMICONDUCTORS

### Usage

1. HPSD warrants that the HPSD products have the specified performance according to the respective specifications at the time of its sale. Testing and other quality control techniques of the HPSD products by HPSD are utilized to the extent HPSD needs to meet the specifications described in this document. Not every device of the HPSD products is specifically tested on all parameters, except those mandated by relevant laws and/or regulations.
2. Following any claim regarding the failure of a product to meet the performance described in this document made within one month of product delivery, all the products in relevant lot(s) shall be re-tested and re-delivered. The HPSD products delivered more than one month before such a claim shall not be counted for such response.
3. HPSD assumes no obligation nor makes any promise of compensation for any fault which should be found in a customer's goods incorporating the products in the market. If a product failure occurs for reasons obviously attributable to HPSD and a claim is made within six months of product delivery, HPSD shall offer free replacement or payment of compensation. The maximum compensation shall be the amount paid for the products, and HPSD shall not assume responsibility for any other compensation.
4. HPSD reserves the right to make changes in this document and to discontinue mass production of the relevant products without notice. Customers are advised to confirm specification of the product of inquiry before purchasing of the products that the customer desired. Customers are further advised to confirm before purchasing of such above products that the product of inquiry is the latest version and that the relevant product is in mass production status if the purchasing of the products by the customer is suspended for one year or more.
5. When you dispose of HPSD products and/or packing materials, comply with the laws and regulations of each country and/or local government. Conduct careful preliminary studies about environmental laws applying to your products such as RoHS, REACH. HPSD shall not assume responsibility for compensation due to contravention of laws and/or regulations.
6. HPSD shall not be held liable in any way for damages and infringement of patent rights, copyright or other intellectual property rights arising from or related to the use of the information, products, and circuits in this document.
7. No license is granted by this document of any patents, copyright or other intellectual property rights of any third party or of HPSD.
8. This document may not be reprinted, reproduced or duplicated, in any form, in whole or in part without the express written permission of HPSD.
9. You shall not use the HPSD products (technologies) described in this document and any other products (technologies) manufactured or developed by using them (hereinafter called "END Products") or supply the HPSD products (technologies) and END Products for the purpose of disturbing international peace and safety, including ( i ) the design, development, production, stockpiling or any use of weapons of mass destruction such as nuclear, chemical or biological weapons or missiles, ( ii ) the other military activities, or ( iii ) any use supporting these activities. You shall not sell, export, dispose of, license, rent, transfer, disclose or otherwise provide the HPSD products (technologies) and END Products to any third party whether directly or indirectly with knowledge or reason to know that the third party or any other party will engage in the activities described above.  
When exporting, re-export transshipping or otherwise transferring the HPSD products (technologies) and END Products, all necessary procedures are to be taken in accordance with Foreign Exchange and Foreign Trade Act (Foreign Exchange Act) of Japan, Export Administration Regulations (EAR) of US, and any other applicable export control laws and regulations promulgated and administered by the governments of the countries asserting jurisdictions over the parties or transaction.